

**DB 200**



5가

- 1 :
- 2 :
- 3 :
- 4 :
- 5 : 2

- 가 : L
- 가 : Leq
- : LE
- : Lpk

& 가

- / ,
- L01-L10-L50-L90
- ,
- 

LDB 200



I/O

0 - 10 V DC

**STANDARDS**

**Sound level meter** : NF EN 61672-1 (2003)- NF EN 60651 (1994) – NF EN 60804 (2000).

**CE conformity** : EN 61010 – EN 61000 generic and as per product standards.



.....	Class 2	Leq	.....	1 ~ 60
.....	Electret ICP - 1/2" -	Lp	.....	1 ~ 60
.....	Sensibility : 15 mV/Pa		.....	LXY - LXYmax - LXYmin -
.....	Free-field		.....	LXeq,T - LXeq,DI - LXE -
.....	Lp/Leq : 100 dB -	Lp & Leq	LXN	LXeq,DImax - LXeq,DImin
	Lpk : 50 dB		.....	LX01 - LX10 - LX50 -
A-가	.....30-130 dB			LX90 - LX95 - resolution 1dB.
C-가	.....35-130 dB			
Z-가	.....35-130 dB			
	.....83-133 dB			
X-가	.....A - C - Z			
Y-가	.....F (fast) - S (slow)			
	.....I (impulse) - Peak (pk)			



..... 240 x 160 -LCD 16  
 & 3D  
 ..... 8  
 .....  
 ..... SD -USB  
 ..... -10 ~ +50  
 ..... 0 ~ 90%RH  
 ..... 270 x 70 x 40mm  
 ( ) ..... 280g  
 .....



5가 ..... - -  
 - S1 + S2  
 ..... L-Leq : 24  
 L-St Leq-St :  
 : 86500 / 25 - : 24 / Leq 1  
 I/O : ..... 0-10V DC : 0-130dB  
 start / stop : TTL 5V  
 : TTL 3.3V  
 .....I/O  
 ..... : 3 x LR6/AA - 15 (20 )  
 - : 24  
 5V , USB



- 
- 
- 3 LR6-AA
- 
- USB
- LDB 200

class 2  
 -  
 - USB  
 I / O

