



DBM610
Airflow meter



: 40 ~ 3500m³/h

PC - 가 (datalogger 10)
가 () / ()
(5가)

DBM 610 - 가 4 610 x 610mm()
가 ()
• 1020 x 1020 mm
• 720 x 720 mm
• 720 x 1320 mm
• 420 x 1520 mm

48

가

() 가

-
- 2



FUNCTIONS

(/)
HOLD 가
PC - USB



•	
	40 ~ 3500 m ³ /h
	3% of the measurement ±10 m ³ /h
	1 m ³ /h

• ()	
	0 ~ 50
	2% of the measurement ±0.1 °C
	0.1°C

• ()	
Thermocouple type	K, J, T, S
	K : -200 ~ +1300 J : -100 ~ +750 T : -200 ~ +400 S : 0 ~ +1760
	K : ±1.1 ±0.4% of reading value J : ±0.8 ±0.4% of reading value T : ±0.5 ±0.4% of reading value S : ±1 ±0.4% of reading value
	0.1°C

•	
	-2500 ~ +2500Pa
	±0.2% of reading ±2Pa
	0.001 ~ 0.1Pa

**All accuracies indicated in this document were stated in laboratory conditions and can be guaranteed for measurements carried out in the same conditions, or carried out with required compensation.*

	LCD (86 × 51mm)
	ABS connectors, Ø 7 x 4 mm
	ABS, IP 54
	12 keys
	Electromagnetical compatibility (NF EN 61326-1 guideline)
	4 LR6 - 3.7V 4400mAh ()
	Neutral gases
	0 ~ 60
	-20 ~ +70
	0 ~ 120
	3600 g

calibration certificate
(610 × 610 mm)

()
: TPL-06-300
SET



WARRANTY

Instruments have 1-year guarantee for any manufacturing defect (return to our After-Sales Service required for appraisal).

